

Brocade BR-1860-1P00 Datablad



Brocade BR-1860-1P00 Single Port 10Gb FCoE CNA, en 10GbE SR SFP+ ingår

BR-1860-1P00

Specifikationer

- Märke: Brocade
- Artikelnummer: BR-1860-1P
- Tillverkare P/N: BR-1860-1P00
- Antal portar/kanaler: 1 port
- Protokoll: FCoE
- Dataöverföringshastighet: 10 Gbps
- Busstyp: PCI Express 2.0 x8

Support för operativsystem

- VMware ESX 3.5
- VMware ESX/ESXi 4.0 , U1, U2
- VMware ESX/ESXi 4.1 , U1
- VMware ESXi 5.0
- VMware ESXi 5.1
- VMware ESXi 5.5
- Microsoft Hyper-V Server 2008
- Citrix XenServer 6.1
- Oracle VM 3.1.1 (eller senare)

- Windows Server 2008 SP1/SP2 (32 bitar)
- Windows Server 2008 SP1/SP2/R2 (64 bitar)
- Windows 7 Enterprise/Windows 7 Enterprise SP1 (32 bitar)
- Windows 7 Enterprise/Windows 7 Enterprise SP1 (64 bitar)
- Windows Server Core (32/64-bitars)
- Windows PE (32 bitar)
- Windows PE (64 bitar)
- Windows Server 2012 (64 bitar)
- Windows Server 2012 R2 (64 bitar)
- Red Hat Enterprise Linux 4.6, 4.7, 4.8, 4.9 (32 bitar)
- Red Hat Enterprise Linux 4.6, 4.7, 4.8, 4.9 (64 bitar)
- Xen för Red Hat Enterprise Linux 5
- Red Hat Enterprise Linux 5.2, 5.3, 5.4, 5.5, 5.6 (32 bitar)
- Red Hat Enterprise Linux 5.2, 5.3, 5.4, 5.5, 5.6 (64 bitar)
- Red Hat Enterprise Linux 5.2, 5.3 (IA64 bit)
- Red Hat Enterprise Linux 5.7, 5.8, 5.9 (32 bitar)
- Red Hat Enterprise Linux 5.7, 5.8, 5.9 (64 bitar)
- Red Hat Enterprise Linux 6.0, 6.1, 6.2, 6.3, 6.4 (32 bitar)
- Red Hat Enterprise Linux 6.0, 6.1, 6.2, 6.3, 6.4 (64 bitar)
- Xen för SUSE Linux Enterprise Server 10
- SUSE Linux Enterprise Server 10 SP1, SP2, SP3, SP4 (32 bitar)
- SUSE Linux Enterprise Server 10 SP1, SP2, SP3, SP4 (64 bitar)
- SUSE Linux Enterprise Server 10.3, 10.4 (32 bitar)
- SUSE Linux Enterprise Server 10.3, 10.4 (64 bitar)
- Xen för SUSE Linux Enterprise Server 11 (32/64 bitar)
- KVM för SUSE Linux Enterprise Server 11 (32/64 bitar)
- SUSE Linux Enterprise Server 11, SP1 (32 bitar)
- SUSE Linux Enterprise Server 11, SP1 (64 bitar)
- SUSE Linux Enterprise Server 11.1, 11.2, 11.3 (32 bitar)
- SUSE Linux Enterprise Server 11.1, 11.2, 11.3 (64 bitar)
- Solaris 10 x86 (32 bitar)
- Solaris 10 x86 (64 bitar)
- Solaris 10 SPARC (64 bitar)
- Solaris 11 x86 (64 bitar)
- Solaris 11 SPARC (64 bitar)
- VMware ESX 4.1 (64 bitar)
- VMware ESX 5.0, 5.1 (64 bitar)

- Oracle Enterprise Linux 5.7, 5.8 (32 bitar)
- Oracle Enterprise Linux 5.7, 5.8 (64 bitar)
- Oracle Enterprise Linux 6.1, 6.2 (32 bitar)
- Oracle Enterprise Linux 6.1, 6.2 (64 bitar)

Mediasupport

- Brocade 10 Gb SFP+ optisk modul, SR (XBR-000180)
- Brocade 10 Gb SFP+ optisk modul, LR, 10 km (XBR-000182)
- Brocade 10Gb SFP+ optisk modul, USR (10G-SFPP-USR)
- Brocade 10 Gb SFP+ direktansluten (Twinax) kabel, 1 m (XBR-TWX-0101)
- Brocade 10 Gb SFP+ direktansluten (Twinax) kabel, 3 m (XBR-TWX-0301)
- Brocade 10 Gb SFP+ direktansluten (Twinax) kabel, 5 m (XBR-TWX-0501)
- Cisco 10 Gb SFP+ direktanslutningskabel (Twinax), 7 m (SFP-H10GB-ACU7M)*
- Cisco 10 Gb SFP+ direktansluten (Twinax) kabel, 10 m (SFP-H10GB-ACU10M)*
- EMC 10 Gb SFP+ direktansluten (Twinax) kabel, 1m (SFP-TWNACT-1M, 038-004-176, 038-003-775)
- EMC 10 Gb SFP+ direktansluten (Twinax) kabel, 3m (SFP-TWNACT-3M, 038-004-177, 038-003-777)
- EMC 10 Gb SFP+ direktansluten (Twinax) kabel, 5m (SFP-TWNACT-5M, 038-004-178, 038-003-779)

Datablad

- [BR-1860-1P00 Datablad](#)

[Köp nu](#)