

Brocade BR-1860-2F00 Datablad



Brocade BR-1860-2F00 Dual port 16Gbps Fibre Channel HBA, SWL SFP+ ingår

BR-1860-2F00

Specifikationer

- Märke: Brocade
- Tillverkare P/N: BR-1860-2F00

- Antal portar/kanaler: 2 portar
- Protokaler: FC/DCB/FCoE/iSCSI
- Dataöverföringshastighet: 16/8/4/2 Gbps
- Busstyp: PCI Express 2.0 x8

Support för operativsystem

- VMware ESX 3.5
- VMware ESX/ESXi 4.0 , U1, U2
- VMware ESX/ESXi 4.1 , U1
- VMware ESXi 5.0
- VMware ESXi 5.1
- VMware ESXi 5.5
- Microsoft Hyper-V Server 2008
- Citrix XenServer 6.1
- Oracle VM 3.1.1 (eller senare)

- Windows Server 2008 SP1/SP2 (32 bitar)
- Windows Server 2008 SP1/SP2/R2 (64 bitar)
- Windows 7 Enterprise/Windows 7 Enterprise SP1 (32 bitar)
- Windows 7 Enterprise/Windows 7 Enterprise SP1 (64 bitar)
- Windows Server Core (32/64-bitars)
- Windows PE (32 bitar)
- Windows PE (64 bitar)
- Windows Server 2012 (64 bitar)
- Windows Server 2012 R2 (64 bitar)
- Red Hat Enterprise Linux 4.6, 4.7, 4.8, 4.9 (32 bitar)
- Red Hat Enterprise Linux 4.6, 4.7, 4.8, 4.9 (64 bitar)
- Xen för Red Hat Enterprise Linux 5
- Red Hat Enterprise Linux 5.2, 5.3, 5.4, 5.5, 5.6 (32 bitar)
- Red Hat Enterprise Linux 5.2, 5.3, 5.4, 5.5, 5.6 (64 bitar)
- Red Hat Enterprise Linux 5.2, 5.3 (IA64 bit)
- Red Hat Enterprise Linux 5.7, 5.8, 5.9 (32 bitar)
- Red Hat Enterprise Linux 5.7, 5.8, 5.9 (64 bitar)
- Red Hat Enterprise Linux 6.0, 6.1, 6.2, 6.3, 6.4 (32 bitar)
- Red Hat Enterprise Linux 6.0, 6.1, 6.2, 6.3, 6.4 (64 bitar)
- Xen för SUSE Linux Enterprise Server 10
- SUSE Linux Enterprise Server 10 SP1, SP2, SP3, SP4 (32 bitar)
- SUSE Linux Enterprise Server 10 SP1, SP2, SP3, SP4 (64 bitar)
- SUSE Linux Enterprise Server 10.3, 10.4 (32 bitar)
- SUSE Linux Enterprise Server 10.3, 10.4 (64 bitar)
- Xen för SUSE Linux Enterprise Server 11 (32/64 bitar)
- KVM för SUSE Linux Enterprise Server 11 (32/64 bitar)
- SUSE Linux Enterprise Server 11, SP1 (32 bitar)
- SUSE Linux Enterprise Server 11, SP1 (64 bitar)
- SUSE Linux Enterprise Server 11.1, 11.2, 11.3 (32 bitar)
- SUSE Linux Enterprise Server 11.1, 11.2, 11.3 (64 bitar)
- Solaris 10 x86 (32 bitar)
- Solaris 10 x86 (64 bitar)
- Solaris 10 SPARC (64 bitar)
- Solaris 11 x86 (64 bitar)
- Solaris 11 SPARC (64 bitar)
- VMware ESX 4.1 (64 bitar)
- VMware ESX 5.0, 5.1 (64 bitar)

- Oracle Enterprise Linux 5.7, 5.8 (32 bitar)
- Oracle Enterprise Linux 5.7, 5.8 (64 bitar)
- Oracle Enterprise Linux 6.1, 6.2 (32 bitar)
- Oracle Enterprise Linux 6.1, 6.2 (64 bitar)

Mediasupport

- Brocade 8Gb SFP+, SWL (XBR-000147, XBR-000163)
- Brocade 8 Gb SFP+, LWL, 10 km (XBR-000153)
- Brocade 16 Gb SFP+, SWL (XBR-000192)
- Brocade 16Gb SFP+, LWL 10Km (XBR-000198)

Datablad

- BR-1860-2F00 Datablad

[Köp nu](#)